



GTI SE 130 shown

2008 | RECREATION

GTI™ SE 155
GTI SE 130



GTI SE 155 shown

technical specifications

DIMENSIONS

Length	127.0 in. (322.5cm)
Width	49.0 in. (124.5cm)
Height	45.9 in. (117.0cm)
Weight (dry)	747 lbs. (338.8kg)
Rider capacity	1, 2 or 3
Fuel capacity	15.9 US gallons (60L)
Storage capacity	12.4 US gallons (46.8L)

ENGINE

Type	155 hp Rotax® 4-TEC® engine	130 hp Rotax 4-TEC engine
Intake system	Naturally aspirated with 52mm throttle body	Naturally aspirated with 52mm throttle body
Bore x stroke	100mm x 63.4mm	100mm x 63.4mm
Displacement	1494cc	1494cc
Compression ratio	10.6:1	10.6:1
Cooling	Closed-loop cooling system	Closed-loop cooling system
Fuel type	Regular unleaded	Regular unleaded

DRIVE UNIT

Propulsion system	Sea-Doo® Direct Drive
Jet pump	Composite/aluminum, axial flow, single stage, large hub with 10-vane stator
Transmission	Direct drive, forward/neutral/reverse
Impeller	Stainless steel

ELECTRICAL

Ignition	Digital inductive
Starter	Electric
Battery	.12 volt

HULL AND COMPONENTS

Type	Progressive-V, composite
Colors [155]	Regal Red or Spring Green
[130]	Regal Red

EQUIPMENT

Tachometer (Information Center)	.STD
Fuel gauge (Information Center)	.STD
Information Center (17 functions)	.STD
D.E.S.S.™	.STD
O.P.A.S.™ system	.STD
Watertight, removable front storage bin	.STD
Sea-Doo Learning Key™ (LK1 or LK2)	.STD
Wide handlebars	.STD

SE PACKAGE (STD)

- Speedometer (Information Center)
- Lake water temperature sensor (Information Center)
- Cut and sew seat
- Adjustable mirrors
- Premium footwell mats
- Fold-down reboarding ladder
- Ski tow eye



standard features

GTI SE 155 GTI SE 130

ENGINE

1494cc four-stroke, SOHC with four valves per cylinder	155 hp Rotax 4-TEC engine provides reliable performance in fresh or salt water, increased torque at low RPM, optimized power at all RPM levels and throttle positions.	130 hp Rotax 4-TEC engine provides reliable performance in fresh or salt water, increased torque at low RPM, optimized power at all RPM levels and throttle positions.
Sea-Doo Learning Key™	LK1 – Limits engine RPM and top speed to about 35 mph. LK2 – Limits engine RPM and top speed to about 45 mph. Options are programmable by dealer.	
Multi-port fuel injection	Better control of exhaust emission and power at all RPM ranges to reduce emissions and reduce fuel consumption.	
Chokeless starting	Simple, user-friendly starting.	
Closed-loop cooling system	Ensures the proper operating temperature at all speeds and improves corrosion durability.	
Water/air separator	Provides maximum airflow to engine and reduces water intrusion.	
Watertight digital ignition	Provides optimal energy for a consistent spark, ensuring maximum performance.	
RPM limiter	Protects engine from over-revving.	
Warning device	Warns operator of engine and exhaust overheating, engine management and system failure.	
Handlebar-mounted start/stop button	Engine starts and stops with single, user-friendly control button.	
Tips Over Protection System (T.O.P.S.™)	Protects engine in case of turn over.	

PROPULSION SYSTEM

Sea-Doo Direct Drive propulsion system	Delivers optimum performance with the Rotax engine.
Forward/neutral/reverse	Improves maneuverability especially around docks and trailer ramps.
Composite/aluminum stator vanes	Handle the high-performance engine without erosion.
Dual automatic vacuum siphon pumps	Continuously remove water entering the engine compartment.
Large diameter drive shaft with crowned spline design	Maintains engine and pump alignment at all operating speeds.
Replaceable urethane wear ring	Provides long impeller life, less maintenance and maximum thrust.
Stainless steel impeller	Delivers improved acceleration, higher top speed and less cavitation.

HULL AND COMPONENTS

Progressive-V, composite	Similar to the GTX hull, the new Progressive-V hull is wider, flatter, more stable and provides a drier ride.
FRP construction	Strong, light and easy to maintain.
Sponsons	For improved handling.
D-Sea-Bel™ system	Sound reduction system for a quieter ride.
Bumpers	Help protect watercraft from damage while tied to a dock or another craft.
Double density comfort hand grips	Provide extreme hand comfort and great looks.
Wide handlebars	Ergonomic design for ease of use and comfort.
Temporary docking loops	Provide access for quick tie-up.

HULL AND COMPONENTS CONTINUED

Reboarding platform	For easy and comfortable mounting of the craft in deep water.
Floating safety lanyard	Stops engine in manual and emergency situations.
Seat strap	Aids in reboarding from water and as a passenger handhold.
Grab handle	For easy reboarding and as a passenger handhold.
Watertight, removable front storage bin	Provides dry storage for luggage and necessities with easy access.
Storage compartment(s)	Room for supplies on extended cruises.
Large glove compartment	A great place to store frequently used items.
Ski eye	Improved for easy and secure attachment of ski rope.
Elevated fuel filler	Easy access and prevents water intrusion while refueling.
Multifunction Digital Information Center	Reports 17 key operating functions: Fuel Level, Low Fuel Level, Low Oil Pressure, Low Voltage, Hi Voltage, Tachometer, Overheat, Hour Meter, Maintenance Info, Speedometer, Error Codes, Check Engine, Lake Temperature, Sensor Check, Key (battery protection), Key (wrong key), L-Key.
Dual drain plugs	Screw type design with built-in retainer for easy removal and installation.
Digitally Encoded Security System (D.E.S.S.™)	Industry's first digitally encoded theft-deterrent system.
External exhaust cooling flush attachment	Easily accessible and fits a common garden hose.
Foam flotation	Ride with security and peace of mind. Meets or exceeds USCG standards.
Operator's guide, instructional video and booklet	Informs you of boating regulations, care, maintenance and operating safety features.
Off-Power Assisted Steering (O.P.A.S.™)	Assists steering during off-power, as well as off-throttle situations.

SE PACKAGE

Adjustable mirrors	Increase field of view.
Cut and sew seat	Ergonomically designed for comfort and great looks providing seating for three.
Premium footwell mats	Offer extra comfort, non-skid surface and great looks.
Fold-down reboarding ladder	Grooved fold-down for easy reboarding.

WARRANTY

BRP limited warranty covers the watercraft for one year. In some markets, the duration of the warranty coverage may differ.