SMAVERICK X3 900 HO

HIGHLIGHTS

DEFIANT

•

- Trademark Can-Am DNA with next generation design
- Low seating position •

• 14-in. Aluminum wheels with 27-in. Maxxis Bighorn† 2.0 tires

Front and rear 18-in. of suspension travel

Ergo-Lok cockpit with four • way adjustable seats

SPECIFIC TO PACKAGE

- 90 hp Rotax® ACE engine
- Advanced airflow dynamics QRS-X transmission

POWERFUL

- PRECISE • TTX suspension
- Ultra efficient and lightweight chassis
 - Sharpest handling features •



• FOX† 2.5 PODIUM Piggyback shocks			
ENGINE	900 H0		
Туре	90 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Triple-cylinder engine, liquid cooled and Donaldson† high-performance air filter		
Fuel Delivery System	Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI)		
Transmission	Quick Response System X(QRS-X) CVT with high airflow, L / H / N / R / P		
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ X auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)		

SUSPENSIONS			
Front Suspension	Double A-arm with sway bar 18-in. (45.7 cm) travel		
Front Shocks	FOX† 2.5 PODIUM Piggyback		
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 18-in. (45.7 cm) travel		
Rear Shocks	FOX† 2.5 PODIUM Piggyback		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers		

Can-Am Red / 90	0	
TIRES / WHEE	LS	
Front Tires	Maxxis Bighorn 2.0† 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)	
Rear Tires	Maxxis Bighorn 2.0† 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)	
Wheels	14-in. (35.6 cm) aluminum	
DIMENSIONS /	CAPACITIES	
LxWxH	131 x 64 x 65 in. (332.7 x 162.5 x 165.1 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	13 in. (33 cm)	
Estimated Dry Weight	1,470 lb (666.9 kg)	
Cage / Chassis	Dual-phase 980 steel, fully welded	
Rack Capacity	200 lb (91 kg) with LinQ [™] quick- attach	
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)	
Fuel Capacity	10.5 gal (40 L)	

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate and quarter-doors
		Instrumentation	Lighter type DC Outlet in central console
		Lighting	LED headlights and tail lights
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
WARRANTY			

Factory	6-months limited warranty	
Extended	Up to 30 months B.E.S.T. coverage	

©2017 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold bendering end but fort while is conted ensire the backtract. Newer engines in a unid expression space. handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



Can-AmOffroad.com