

2015 SUMMIT® SP



PACKAGE HIGHLIGHTS

- REV-XM™ platform
- tMotion™ rear suspension
- Lightweight chromoly front suspension lower A-arms
- Pilot® DS 2 skis
- Adjustable, narrow ski stance
- Brembo racing brake with braided stainless-steel brake line
- Lightweight, low-profile REV-XM seat with 3 L / 0.8 gal of storage
- RER™ electronic reverse
- Ergonomic, multifunction digital gauge with display and engine temperature gauge
- 12 in. / 28.5 cm windshield

- Warm glove box with 4 L / 1 gal of storage
- Running boards with large opening
- **RF D.E.S.S. key**
- Stiffer grab handle on handlebar
- S-36 handling package

EXTRA HIGHLIGHTS

600 H.O. E-TEC®

- 16 x 146 / 154 x 2.5-inch PowderMax® 2 FlexEdge track (short rods)

800R E-TEC

- 16 x 146 / 154 / 163 x 2.5-inch PowderMax 2 FlexEdge track (short rods)

NEW features for 2015

ENGINE CHOICE

Engine	Rotax® 600 H.O. E-TEC	Rotax 800R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, 3-D R.A.V.E.
Cylinders	2	2
Displacement	594.4cc / 36.3 in³	799.5cc / 48.8 in³
Bore	72 mm / 2.8 in.	82 mm / 3.2 in.
Stroke	73 mm / 2.9 in.	75.7 mm / 3 in.
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection
Recommended fuel type	Premium unleaded	Premium unleaded
Minimum octane	91	91
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.7 liters / 3.9 quarts

POWERTRAIN

Drive clutch type	TRA™ III	TRA VII
Driven clutch type	QRS	QRS
Engagement	4000 RPM	3800 RPM
Small sprocket number of teeth	19	21 (146 in.) 19 (154 in. - 163 in.)
Large sprocket number of teeth	49 (146 in.) 51 (154 in.)	49 (146 in. - 154 in.) 51 (163 in.)
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo racing brake with braided stainless-steel brake line	Brembo racing brake with braided stainless-steel brake line

DRY WEIGHT

206 kg / 454 lb (146 in.)	208 kg / 459 lb (146 in.)
207 kg / 456 lb (154 in.)	210 kg / 464 lb (154 in.)
	213 kg / 469 lb (163 in.)

FEATURES

Frame	REV-XM	Riser block height	205 mm / 8 in.	Mirrors	Optional
Skis	Pilot DS 2	Electric start	Optional	Windshield	285 mm / 12 in.
Seating	REV-XM light weight with storage	Reverse	RER	Carbide runner	Standard
Handlebar	Aluminum with J-hooks / Grab handle	Heated throttle lever	Standard	Carbide configuration	102 mm / 4 in. square type at 90°
		Heated grips	Standard	Hitch	Optional
		Gauge	Multifunction		

©2014 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.



tMotion suspension

A swiveling rear arm and split front arm allow the skid to flex laterally for more predictable carving. A more rising-rate motion ratio adds capacity and comfort.



Low-profile REV-XM seat

Extremely narrow in front and low profile for easily passing legs from side to side. 3.2 L (0.8 gal) of storage in seat base.



Steering and flat gauge

Lightweight and trick looking handlebars. Rigid grab strap offers more leverage and confidence in tricky maneuvers.



Multifunction gauge with LCD display

COLORS AVAILABLE

Lava Red / Black

Black

ENGINE CHOICE

600 H.O. E-TEC

800R E-TEC

GAUGE FEATURES

Speedometer	Standard
-------------	----------

Tachometer	Standard
------------	----------

Fuel	Standard
------	----------

Temperature	Standard
-------------	----------

2015 **SUMMIT SP**